


8MP / 5MP / 4MP / 3MP 1080P/960P/720P **HD NVR**

HV-N9100-32H4-K **HD NVR**





H.265

1080p



AUDIO











Features


- ✓ Support 32CH 8MP/6MP/5MP/4MP/3MP/1080P/ 960P/720P/960H/DI/CIF IP input
- ✓ Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- ✓ Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- ✓ Multi-mode recording: manual / timer / motion / sensor/smart events
- ✓ Playback : 16CH simultaneous playback
- ✓ Search: time slice, time, event, tag, smart search
- Express and flexible backup via USB, network and so on
- ✔ Pentaplex: preview, record, playback, backup and remote access
- ✓ DHCP, DDNS, PPPoE network protocol and CMS supported
- ✓ Remote control via Web or CMS: preview, playback, backup, PTZ and configuration
- ✓ Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- ✓ Multi-user online simultaneously
- Authorization management, log view and device status view
- ✓ 4K ultra high resolution output, true high resolution display
- ✓ Support NAT function and QRCode scanning by mobile phones
- ✔ Powerful mobile surveillance by smart phones with iOS and Andriod OS

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.





Technical Specification HV-N9100-32H4-K



Model		HV-N9100-32H4-K	
System	Compression	Standard H.265 / H.264	
	OS	Embedded Linux	
Video	Network Input	32 CH IPC input	
	Network Input Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/960H/D1/CIF	
	Output	HDMI × 1: 3840 × 2160 /1920 × 1080 / 1280 × 1024/ 1024 × 768 VGA: 1920 × 1080 / 1280 × 1024/ 1024 × 768	(0)5)
Audio	Network Input	32 CH IPC audio input	700)
	2-way Audio	RCA×1	
	Local Output	RCA × 1	
	Compression	G.711(U/A)	
Live View	Decoding Capability	1CH 8MP; 4CH 1080P	
Record	Record Stream	Dual stream recording	
	Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/960H/D1/CIF	
	Frame Rate	P:25fps; N:30fps	
Playback	Simultaneous Playback	Max. 16 CH	
	Search	Time slice / time / event / tag search	
	Smart Search	Highlighted color to display the camera record in a certain perio colors refers to different record events	d of time, different
	Function	Play, pause, FF, FB, digital zoom, etc.	
Alarm	Mode	Manual, sensor, motion, exception, smart events	
	Input	Support 4CH alarm input; Support IPC alarm input	
	Output	Support 1CH alarm output; Support IPC alarm output	
	Triggering	Record, snap, preset, e-mail, etc.	
Network	Interface	RJ 45 1000Mbps × 1	\triangle
	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP	$I(I \cap I)$
	Access/Transfer Bandwidth	112/112 (Mbps)	
Mobile Device	OS	iOS, Andriod	
Storage	HDD	SATA 3.0 × 4, max 8T per HDD	
Backup	Local Backup	U disk, USB mobile HDD	
	Network Backup	Yes	
Port	USB	USB 2.0 \times 2 (one in the front panel and the other in the rear panel	el)
	RS 485	RS 485 \times 2; connect to PTZ or keyboard	
	Remote Controller	Optional	
Others	Power Supply	ATX 250W	
	Consumption	≤ 15W (without HDD)	
	Dimensions (mm)	440 × 390 × 70 (W × D × H)	
	Work Environment	-10 ~ 50 °C, 10% ~ 90% humidity	

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary.



SALES: 011-47097440 | SALES EMAIL: INFO@HAWKVISIONINDIA.COM | SUPPORT EMAIL: SUPPORT@HAWKVISIONINDIA.COM