

Digital Video Recorder HV-D5100-8HL 1080P Hybrid DVR





Features

- ✓ 8 CH TVI / AHD/CVI 1080P/1080PLite/720P/720P Lite/WD1 video input
- ✔ 8 CH DVR supports 2 / 2 CH 5MP / 4MP / 3MP /1080P / 960P /720P IP video input by default
- 8 CH DVR default supports 8 CH analog input switched to IP input Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- ✓ Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timed/ motion / Al recording Playback : 8 CH simultaneously playback
- Search: time slice, time, event, tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- ✔ DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Authorization management, log review and device status review
- ✓ Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phones
- ✓ Powerful mobile surveillance by smart phones with iOS and Andriod OS

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

www.hawkvisionindia.com



CCTV CAMERAS | NVR & DVR SERIES | ATTENDANCE MACHINES & ACS | VDP SERIES



Technical Specification HV-D5100-8HL

9

Model		HV-D5100-8HL
System	OS	Embedded Linux
Video	Analog Video Input	BNC × 8, BNC interface (1.0Vp-p; 75Ω) TVI/ AHD/CVI: 1080P/ 1080P Lite/ 720P/ 720P Lite/ WD1
	IP Video Input	2CH (up to 10CH), Up to 5MP@25fps/4MP@30fps
	Total Input	10CH
	Output	HDMI × 1 :1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 CVBS: No
	Compression	H.264/H.265
	Multi-screen Display	1/4/6/8/9/13/16
Audio	Input/ Output	RCA ×1/ RCA × 1 (linear, 600Ω)
	Two-way audio	Take up channel one audio input
	Compression	G.711(U/A)
Record	Resolution	1080P Lite/ 720P/ 720P Lite/ WD1
	Frame Rate	Analog Channel: 1080P Lite/720P: 25fps (PAL)/30fps (NTSC) (only CH 1 supports) 1080P Lite/720P: 12fps (PAL)/15fps (NTSC) (other channels support) 720P Lite/WD1: 25fps(PAL) / 30fps (NTSC) IP Channel: 25fps(PAL) / 30fps (NTSC)
	Bit Rate	32Kbps ~ 4Mbps
Playback	Playback	8CH
	Search	Time slice / time / event / tag search
	Smart Search	Highlight colors to display the camera record in a certain period of time, different colors refer to different record events
	Function	Play, pause, FF, FB, digital zoom, etc.
Alarm	Mode	Manual, motion, exception, smart event
	Input/ Output	No
Network	Interface	RJ 45 100Mbps × 1
	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPs, NTP, SMTP
	Incoming/ Outgoing Bandwidth	16Mbps (Max. 56Mbps)/ 60Mbps
	Client Connection	Max. 5 users access
Mobile Device	OS	iOS, Andriod
Storage	HDD	SATA× 1, up to 6TB
Backup	Local Backup	U disk, USB mobile HDD
	Network Backup	Yes
Port	RS 485/ Remote Controller	No
	USB	USB 2.0 × 2
Others	Power Supply	DC12V / 1.5A
	Consumption	≤ 5W (without HDD)
	Dimensions(mm)	255 × 222 × 42 (W × D × H)
	Working Environment	-10~50°C, 10%~90% (humidity)
	Certificate	CE, FCC

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

AAA SECURITY SOLUTIONS: 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034 SALES: 011-47097440 | SALES EMAIL: INFO@HAWKVISIONINDIA.COM | SUPPORT EMAIL: SUPPORT@HAWKVISIONINDIA.COM

