

# Speed Dome IP PTZ Camera

### HV-IP-PTZ-6620-18X PTZ Camera











#### DEFOG HLC

### **Features**

- ✓ Adopt SONY high performance 1/2.8″
- ✓ Support dual stream compression technology.
- Rotate 360°in horizontal direction, driven by exact engine, operate stably with Precise position-setting.
- The rotation speed can be adjustable according to the zoom rate of camera lens, auto-focus, auto white balance.
- ✓ Vertical 90° continuous monitoring after auto reversing 35°.

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

www.hawkvisionindia.com



#### CCTV CAMERAS | NVR & DVR SERIES | ATTENDANCE MACHINES & ACS | VDP SERIES



## Technical Specification HV-IP-PTZ-6620-18X



Model No .	HV-IP-PTZ-6620-18X	
Signal model	PAL/NTSC	_
Image sensor	1/2.8" SONY	
Effective pixel	1920*1080	
Horizontal resolution	1080P	$\overline{)}$
Minimum illumination	Color to B/W,Color:0.1Lux,B/W:0.01Lux	1
S/N ratio	>60dB(Enhanced)	1
Backlight compensation	On/Off	_
White balance	Auto	
Electronic shutter	PAL:1/25~1/100000s NTSC:1/30~1/100000s	
Focus length	5~90mm	1
Optical focus	18X	
Focus	Auto / Manual / Push Auto , the use of high-performance DSP to realize complete digit and ultra- high speed focus function	7
Presets	255	
IR distance	100m	
Patrol Track	2 groups,each can record 3mins	)
Other scan	Support Horizontal scan, deuce area scan, scan random	
Rotation range	Horizontal 360° unlimted rotation, Vertical 90°, auto reversal	
Rotation speed	Horizontal & Vertical Min 0.01°,Max 35°/S	
Video compression	H.265 Main Profile encoding ; MJPEG / JPEG Baseline encoding	)
Audio compression	G.711, G.726	1
Primary stream	1920*1080, 25fps	5
Secondary stream	VGA QVGA	
Video bit rate	32Kbps-16Mbps continuously adjustable, support CBR / VBR	
Network protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP	
ONVIF support	Support	
Power supply	DC12V/3A	
Work environment	-20°C~+50°C (select temperature control accessories), <95%RH	

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

AAA SECURITY SOLUTIONS: 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034 SALES: 011-47097440 | SALES EMAIL: INFO@HAWKVISIONINDIA.COM | SUPPORT EMAIL: SUPPORT@HAWKVISIONINDIA.COM