

2MP 25X Starlight IR Network PTZ Camera

HV-IP-PTZ-6620S-AI-25X PTZ Camera









HD

, <u>,,,,,</u>

DAY & NIGH



POE

GHT











HLC

C VCA

Features

- ✓ 1/2.8" progressive scan CMOS
- ✓ Up to 1920×1080 resolution
- ✓ Mini illumination: Color: 0.005 lux @ (F1.6 AGC ON) B/W: 0.001 lux@ (F1.6 AGC ON); 0 Lux with IR
- ✓ 25x optical zoom, 16x digital zoom
- ✓ 120 dB WDR, 3D DNR, Smart IR
- ✓ Up to 150m IR distance
- ✓ Smart H.265/H.264 video compression
- ✓ 0.5Tops Deep-learning Engine
- ✓ Smart tracking of human/vehicle
- Smart detection and perimeter protection
- ✓ IP66,-30°C~ 60°C, Aluminum Alloy &Plastic
- ✔ PoE+ (802.3.at, class 3) and DC24V/AC24V
- ✓ ONVIF, API and SDK

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.





Technical Specification HV-IP-PTZ-6620S-AI-25X



Model	HV-IP-PTZ-6620S-AI-25X	
System	Hi3516CV500, 8Gb LPDDR3,2Gb SPI Flash, product active till 2022,Dec.	
Image sensor	1/2.8" progressive scan CMOS(SONY IMX462)	
Mini. Illumination	Color 0.005Lux @ (F1.65 AGC ON) B/W 0.001Lux @(F1.65 AGC ON);0Lux with IR	
Image setting	Flip, Mirror, Saturation, Brightness, Contrast, Sharpness, AGC, and AWB adjusted by sof	tware/browser
Shutter Speed	1/1 s – 1/10,000 s	
White Balance	Auto/Manual/Indoor/Outdoor	(01)
Gain	Auto/Manual	700)
Day & Night	IR Cut filter	
Digital Zoom	16x	
Privacy Mask	4 Programmable privacy masks	
3D DNR	Auto/Manual	
BLC/ HLC	Yes	
WDR	120 dB	
Defog	Electronic	
EIS	Yes	\supset
Regional Exposure	No	
Picture overlay	Logo picture could be overlaid on video with 128x128pixels, 24bits BMP format	
Lens		
Focus length	F=4.8-120mm lens,25x optical zoom	
Zoom Speed	Approx. 3.6s (optical zoom, wide-tele)	
Field of View	Horizontal: 57.6°to 2.5°(wide -tele); Vertical: 34.4°to 1.4°(wide -tele); Diagonal: 64.5	°to 2.9°(wide -tele)
Working distance	wide: 1.0m ~ INF; tele: 1.5m ~ INF	
Aperture Range	F1.65 ~ F3.8 (wide-tele)	
PTZ		
Pan Range / speed	360° endless / Configurable, from 0.1~80°/s; Preset speed: 150°/s	\triangle
Tilt Range / Speed	From -3°to 90° / Configurable, from 0.1°~ 80°/s, Preset speed: 120°/s	
Proportional Zoom	Yes	
Preset	360	
Cruise	8 cruises, up to 16 presets for each cruises	
Track	4 tracks, record time over 3 minutes for each track	
Power off memory	Support	
Action mode	Preset/Cruise/Track/Auto Scan/Random Scan	
3D Positioning	Support	
PTZ Position Display	Support	
Schedule Task	Preset/Cruise/Track/Random Scan/Boundary Scanning / Dome reboot	
IR		
IR Distance	150m (492 f.t.)	
Smart IR	Yes, support facial exposure	

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

AAA SECURITY SOLUTIONS: 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034
SALES: 011-47097440 | SALES EMAIL: INFO@HAWKVISIONINDIA.COM | SUPPORT EMAIL: SUPPORT@HAWKVISIONINDIA.COM





Technical Specification HV-IP-PTZ-6620S-AI-25X



Network	
Max Resolution 1920×1080	
Main stream 1920×1080,1280×960,1280×720 (25/30fps)	
Sub stream 25fps (704 × 576, 640 × 480, 352 × 288); 30fps (704 × 480, 640 × 480, 352 × 240)	
Third Stream 25fps (1920 ×1080, 1280 ×960, 1280 ×720, 70 4 ×576, 640 ×480, 352 ×288) 30fps (1920 ×1080, 1280 ×960, 1280 ×720, 704 ×480, 640 ×480, 352 ×240)	
SVC Yes	
Video compression Smart H.265+/H.265/H.264/MJPEG	
Audio compression G.711 A/U	
ProtocolsHTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTUDP, IGMP, ICMP, DHCP, PPPoE	SP, RTCP, RTP, TCP/IP,
Simultaneous live view Up to 6 channels	
User / Host Up to 16 users, 3 levels: Administrator, Advanced User and Normal User	
Security Measures User authentication (ID and PW), Host authentication (MAC address); HTTPS end port-based network access control; IP address filtering	cryption, IEEE802.1x
Smart Features	
Basic event Motion detection, video tampering alarm, exception (network disconnected, IP full, SD error), defocus detection	address conflict, SD
Face Recognize /Compare Default off, max 15 human faces per second.	
People Density/LPR Not support by this product	
Smart Detection Intrusion detection, Line crossing detection, Region entrance detection, Region Unattended baggage detection, Object removal detection, Scene change detecting triggering by human or vehicle, filtering flag/animal.	
Smart Tracking Manual Tracking, Auto Tracking (human or vehicle by software setting)	
System Integration	
Alarm Interface 1 Alarm input;1 Alarm output	
Audio Interface 1 audio input(mic in); 1 audio output, line level, impedance,600Ω	
Alarm Linkage Alarm actions, such as Preset, Cruise, Track, Memory Card Video Record, Trigger Surveillance Center, Upload to FTP/Memory Card, Send Email, etc.	Recording, Notify
Network Interface1 RJ45 10M/100M Adaptive Ethernet (Support PoE 802.3.at,class 3)	
CVBS/ RS 485 None	
SD Card Slot One MicroSD/SDHC/SDXC card slot, up to 256G	
Web Browser IE8-11, Chrome41.0-44, Firefox30.0-51, Safari8.0-11	
General	
Power DC24V,AC24V or PoE+ (802.3.at, class 3), (Max 30W, include IR, Heater, Fan working, max 9W for IR)	
Working condition $-30^{\circ}\text{C} \sim 60^{\circ}\text{C} \text{ (} -22^{\circ}\text{F} \sim 140^{\circ}\text{F)},90\%\text{RH less (non -condensing),Cold start at - 25^{\circ}\text{C}}$	
Storage condition $-40^{\circ}\text{C} \sim 65^{\circ}\text{C}$; $\leq 95\%$ RH	
Protection IP66, 6000V Lightning Protection, Surge Protection and Voltage Transient Protection	ction
Material Aluminum Alloy + Plastic	
Material Aluminum Alloy + Plastic Dimensions Φ 209mm × 328mm (8.22" Φ × 12.91")	

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary.

All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

AAA SECURITY SOLUTIONS: 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034 SALES: 011-47097440 | SALES EMAIL: INFO@HAWKVISIONINDIA.COM | SUPPORT EMAIL: SUPPORT@HAWKVISIONINDIA.COM

